

STATIC NON-FLUSH



The Basic Non-Flush features one single toilet and a urinal. For special occasions, we offer the option of adding a hand sanitizer or one of our Handi-Wash stations for a more sanitized surrounding.

For elevated construction sites, like buildings, the Basic Non-Flush can be equipped with a sling to allow lifting by crane.

Servicing is fulfilled on-site by our trained technicians. It includes cleaning the restroom, the removal of waste from the tank and restocking the supplies as required. We offer flexible service time frames to suit your schedule. Whether it is daily, weekly or monthly, you let us know! Our technicians document all service stops inside the unit for your review and convenience.

24/7 emergency service is available.

>> DIMENSIONS

- External 43.5" X 47" X 91"
- Weight 189lbs
- Waste capacity 50 gallons

>> INCLUDED EQUIPMENT

- Non-flush tank with seat
- Oversized urinal to help maintain cleanliness
- Toilet paper

>> NOTES

- Non-Flush Static Toilet
- Heat-treated aluminum doorjamb designed to withstand frontal impact
- Tall door
- Angled vents to help keep precipitation out of toilet
- Exhaust port directed from the waste tank to the outside to help lower the odour from the unit

Our basic Non-Flush model continues to set the standard for utility, quality and ease of use. It can be found anywhere from construction sites to special occasions.

>> INCLUDED IN OUR SERVICES

- Emptying of waste
- Restocking of toilet Paper supplies
- Washing the toilet and floor
- Client is responsible for disposal of garbage

>> WINTER

- A salt water brine is placed in unit to avoid freeze up

