

REGULATION FLUSH TOILET WITH SINK



The regulation unit was created to meet the Ontario Ministry of Labour standards act and provide a more sanitary environment for workers.

This unit is operated by foot or pump for flush and wash controls which increase the levels of sanitation.

For elevated construction sites, like buildings, the Regulation unit can be equipped with a sling to allow lifting by crane.

Servicing is fulfilled on-site by our trained technicians. It includes cleaning the restroom, the removal of waste from the tank and restocking the supplies as required. We offer flexible service time frames to suit your schedule. Whether it is daily, weekly or monthly, you let us know! Our technicians document all service stops inside the unit for your review and convenience.

24/7 emergency service is available.

>> DIMENSIONS

- External 43.5" X 47" X 91"
- Weight 189lbs
- Waste capacity 50 gallons
- Fresh water capacity 16 gallons

>> INCLUDED EQUIPMENT

- Recirculating flush tank with seat
- Oversized urinal to help maintain cleanliness
- Foot pedal activated Sink
- Toilet paper
- Paper Towel
- Soap
- Heater (during winter months)

>> NOTES

- Recirculating flush toilet
- Fresh water sink with soap & paper towels
- Heat-treated aluminum doorjamb designed to withstand frontal impact
- Tall door
- Angled vents to help keep precipitation out of toilet
- Exhaust port directed from the waste tank to the outside to help lower the odour from the unit

>> INCLUDED IN OUR SERVICES

- Emptying of waste
- Re-filling the fresh water
- Restocking of soap, paper & toilet Paper supplies
- Washing the toilet and floor
- Client is responsible for disposal of garbage

>> WINTER

- A salt water brine is placed in unit to avoid freeze up
- Sanitizer installed during winter period